

Clamcleat® Rope cleats

CK Cleat Range

Performance cleating for Control Lines

clamcleat.com/ck

High quality, marine grade, stainless steel, aluminium and engineering plastics. Cleats available in silver or hard anodised finish.

Cage provides alignment and cleating from a distance.

Rear fairlead gives cleating angles up to 70°

Keeper automatically keeps rope in or out of cleat.

Alloy cleat.
No moving parts.
Positive rope grip.

Keeper allows rope to run free when uncleated.

Positive click when rope is cleated.

Lift up to release. **Keeper** opens to allow rope out of teeth.

Rope gripped. **Keeper** holds rope in cleat.

CL825CKC silver CL825CKCAN Hard Anodised

Two cleats pre-assembled onto tapered base. Fit new or replace CL211 Mk1 without drilling new holes.



3-6 mm	M5	4.8 mm	150 gms
1/8-1/4"	#10, 3/16"	N°10	5.3 ozs

CL833CKC silver CL833CKCAN Hard Anodised


Use as a new fitting or to replace CL211 Mk1 without drilling new holes.



3-7 mm	M5	4.8 mm	75 gms
1/8-1/4"	#10, 3/16"	N°10	2.7 ozs

CL830CKC silver CL830CKCAN Hard Anodised

Side fixing cage allows cleat to be used as a direct replacement to cams.



3-6 mm	M4	4.2 mm	58 gms
1/8-1/4"	#8, 5/32"	N°8	2.0 ozs

CL832CKC silver CL832CKCAN Hard Anodised

Use as a new fitting or to replace CL211 Mk2 without drilling new holes.



3-6 mm	M4	4.2 mm	51 gms
1/8-1/4"	#8, 5/32"	N°8	1.8 ozs

Clamcleat®
Rope cleats
clamcleat.com/ck

Two cleats - Only one set of fixing holes.

Cleat angles up to 70°

Automatically keep rope in or out of cleat.

78 mm 3 1/16"

66 mm 2 5/8"

Hole centres same as CL211 Mk1

88 mm 3 7/16"

Clamcleat®
Rope cleats
clamcleat.com/ck

Cleat angles up to 70°

Automatically keep rope in or out of cleat.

29 mm 1 1/8"

89 mm 3 1/2"

66 mm 2 5/8"

Hole centres as CL211 Mk1

Clamcleat®
Rope cleats
clamcleat.com/ck

Side fixing = direct Cam replacement.

Cleat angles up to 70°

Automatically keep rope in or out of cleat.

44 mm 1 3/4"

62 mm 2 7/16"

27 mm 1 1/16"

Hole centres

Clamcleat®
Rope cleats
clamcleat.com/ck

Cleat angles up to 70°

Automatically keep rope in or out of cleat.

27 mm 1 1/16"

61 mm 2 7/16"

Hole centres as CL211 Mk2